



BS782496

Cylinder Cart with Firewall and Lifting Eye

Features

- Full range, high rail with lifting eye
- Large, open tool tray
- Reinforced lifting eye and dual cylinder arms offer some of the best safety in its class!
- Safely move compressed gas cylinders around your facility transporting oxygen cylinder together with a fuel cylinder at the same time.
- Lifting eye complies with ASME B30.20, AWS D14.1 and AISC codes and the Fire-rated wall complies with OSHA 1926.350 and OSHA 1910.253
- Reinforced lifting eye offers added safety and security over leading competitors

Technical Specifications

- **Material:** Powder Coated Iron
- **Color:** Green
- **Number of Cylinders per Unit:** 2
- **Handle Type:** Curved
- **Dimensions:** 36.8" W x 66.5" H x 22.1" D
- **Firewall:** 60" x 1.18"
- **Base Plate:** 26.5" x 13.18" (63 cm x 33 cm)
- **Wheel Type:** 16" x 4" Foam Filled Pneumatic Flat Free
- **Oxygen Cylinder:** Supports 244-330 ft³ (9 1/4") tank
- **Acetylene Cylinder:** Supports 210-420 ft³ (13 1/2") tank
- **Packaging:** Packaged Individually
- **Country of Origin:** India

Applications

- Manufacturing – Architectural and Structural Metals, Mining, Agricultural, Motor Vehicles, Aerospace, Shipbuilding
- Construction – Residential, Commercial, Bridges, Dams, Utilities
- Or any other industry where welders may work

Usage Instructions

- Place cylinder cart near compressed gas cylinders
- Remove cylinder brackets from cart
- Place compressed gas cylinders on cart
- Put back cylinder brackets to secure compressed gas cylinders to cart
- From behind the cart, use lifting eye to pull the top part of the cart towards you while bracing the base with your foot providing an equal weight distribution on the wheels
- Safely walk to transport the gas cylinders with one hand on the lifting eye and the other on the rail