## **SPECIFICATION SHEET**

## TECHNIWELDUSA



# SS45002

#### 4.5" Cut Off Wheel

Features	<b>Technical Specifications</b>
<ul> <li>Designed with a specialty and proprietary combination of virgin grains from very high-quality ceramic and aluminum oxide.</li> <li>Excels on stainless, carbon steel, rebar, high alloy, and plastics, as well as other non-ferrous metals.</li> <li>0.045" cut off wheels allow minimal resistance for very high-speed cutting.</li> <li>Used for cutting ferrous metals like iron, steels, welds, rebar.</li> </ul>	<ul> <li>Material: Ceramic/Aluminum Oxide</li> <li>Color: Black</li> <li>Size: 4.5" x 0.045" x 0.875"</li> <li>Diameter: .045"</li> <li>Bore: 7/8"</li> <li>Weight: .22 lbs.</li> <li>Type Number: Type 27</li> <li>Max RP: 13300</li> <li>Packaging: 50 per pack</li> <li>Country of origin: USA</li> </ul>

#### **Applications**

### Usage Instructions

Cutting
Grinding
Paint removal
Deburring
For use with Angle Grinder.
Carefully install cutting wheel on the grinder and lock it into place.
Make contact with the material and grind through the surface.

TECHNIWELDUSA / www.

WWW.TECHNIWELDUSA.COM

6205 Boat Rock Blvd. SW, Atlanta, Georgia 30336-2727 | Toll Free: (800) 445-2152

2 | Fax: (404) 699-7800