



AG146050WBA

14oz Black Neoprene/Acrylic Coated
Fiberglass Fabric

Features

- High-temperature resistant black neoprene/acrylic coated fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 25 rolls per pallet.

Technical Specifications

- **Weave:** 3x1 TWILL
- **Yarn:** WARP: EC9 68 1x2 tex; WEFT: EC9 68 1x2 tex
- **Length:** 50 yds
- **Width:** 60"
- **Weight as per ASTM-D3776-2009:** 430 g/m² (12.68 oz/yd²)
- **Ounces per Square Yard:** 14
- **Thickness as per ASTM-D1777-1996:** 0.4 mm (0.0157")
- **Thread count per cm as per ASTM-D3775-2008:** WARP: 18; WEFT: 13
- **Coating:** Neoprene/Acrylic coated, Black
- **Total Weight as per ASTM-D3776-2009:** 430 g/m² (12.68 oz/yd²)
- **Total Thickness as per ASTM-D1777-1996:** 0.4 mm (0.0157")
- **Tensile Strength as per ASTM-D5034-2001:** WARP: 2000 N/2.5 cm; WEFT: 1500 N/2.5 cm
- **Fabric Temperature Rating:** 550°C (1022°F)
- **Coating Temperature Rating:** 107°C (225°F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, America FM/ANSI 4950