



# AG246050WBA

## 24oz Black Neoprene/Acrylic Coated Fiberglass Fabric

### Features

---

- High-temperature resistant black neoprene/acrylic coated fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 16 rolls per pallet.

### Technical Specifications

---

- **Weave:** PLAIN
- **Yarn:** **WARP:** ET9 430 tex; **WEFT:** ET9 430 tex
- **Length:** 50 yds
- **Width:** 60"
- **Weight as per ASTM-D3776-2009:** 580 g / m<sup>2</sup>
- **Ounces per Square Yard:** 24
- **Thickness as per ASTM-D1777-1996:** 0.75 mm
- **Thread count per cm as per ASTM-D3775-2008:** **WARP:** 8; **WEFT:** 5.7
- **Coating:** Neoprene/Acrylic Coated, Black
- **Coating Weight as per ASTM-D3776-2009:** 200 g / m<sup>2</sup>
- **Total Weight as per ASTM-D3776-2009:** 780 g / m<sup>2</sup>
- **Total Thickness as per ASTM-D1777-1996:** 0.95 mm
- **Tensile Strength as per ASTM-D5034-2001:** **WARP:** 1320 N/2.5 cm; **WEFT:** 880 N/2.5 cm
- **Fabric Temperature Rating:** 550°C (1022°F)
- **Coating Temperature Rating:** 107°C (225°F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE