



AGWB166X6PA

16oz Pink Neoprene/Acrylic Coated Fiberglass Welding Blanket

Features

- High-temperature resistant pink neoprene/acrylic coated fiberglass welding blanket.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 10 pieces per box, 27 boxes per pallet.

Technical Specifications

- **Weave:** PLAIN
- **Yarn:** **WARP:** ET9 68 1x3 tex; **WEFT:** ET9 68 1x3 tex
- **Length:** 6 ft
- **Width:** 6 ft
- **Weight as per ASTM-D3776-2009:** 400 g / m²
- **Ounces per Square Yard:** 16
- **Thickness as per ASTM-D1777-1996:** 0.4 mm
- **Thread count per cm as per ASTM-D3775-2008:** **WARP:** 12; **WEFT:** 8
- **Coating:** Neoprene/Acrylic Coated, Pink
- **Coating Weight:** 100 g / m²
- **Total Weight as per ASTM-D3776-2009:** 500 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 0.5 mm
- **Tensile Strength as per ASTM-D5034-2001:** **WARP:** 2200 N/2.5 cm; **WEFT:** 1870 N/2.5 cm
- **Fabric Temperature Rating:** 550°C (1022°F)
- **Coating Temperature Rating:** 107°C (225°F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, American FM/ANSI 4950