



AGWB186X6TU

18oz Tan Uncoated Fiberglass Welding Blanket

Features

- High-temperature resistant tan uncoated fiberglass welding blanket.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 6 pieces per box, 27 boxes per pallet.

Technical Specifications

- **Weave:** PLAIN
- **Yarn:** **WARP:** ET9 430 tex; **WEFT:** ET9 430 tex
- **Length:** 6 ft
- **Width:** 6 ft
- **Weight as per ASTM-D3776-2009:** 580 g / m²
- **Ounces per Square Yard:** 18
- **Thickness as per ASTM-D1777-1996:** 0.75 mm
- **Thread count per cm as per ASTM-D3775-2008:** **WARP:** 8; **WEFT:** 5.7
- **Coating:** Uncoated, Tan
- **Total Weight as per ASTM-D3776-2009:** 580 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 0.75 mm
- **Tensile Strength as per ASTM-D5034-2001:** **WARP:** 1200 N/2.5 cm; **WEFT:** 800 N/2.5 cm
- **Fabric Temperature Rating:** 550°C (1022°F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, American FM/ANSI 4950