



AGWB246X60U

24oz Orange Uncoated Fiberglass Welding Blanket

Features

- High-temperature resistant orange uncoated fiberglass welding blanket.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 10 pieces per box, 18 boxes per pallet.

Technical Specifications

- **Weave:** PLAIN
- **Yarn:** WARP: ET9 860 tex; WEFT: ET9 860 tex
- **Length:** 6 ft
- **Width:** 6 ft
- **Weight as per ASTM-D3776-2009:** 815 g / m²
- **Ounces per Square Yard:** 24
- **Thickness as per ASTM-D1777-1996:** 1 mm
- **Thread count per cm as per ASTM-D3775-2008:** WARP: 6; WEFT: 3.4
- **Coating:** Uncoated, Orange
- **Total Weight as per ASTM-D3776-2009:** 815 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 1 mm
- **Tensile Strength as per ASTM-D5034-2001:** WARP: 1500 N/2.5 cm; WEFT: 1000 N/2.5 cm
- **Fabric Temperature Rating:** 550°C (1022°F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, American FM/ANSI 4950