



AGWB189X10TC

18oz Tan Silica Fiberglass Fabric Welding Blanket

Features

- High-temperature resistant tan silica fiberglass fabric welding blanket.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Packaged individually, 4 pieces per box, 18 boxes per pallet.

Technical Specifications

- **Weave:** 8HS SATIN
- **Yarn:** **WARP:** EC9 136 1x2 tex; **WEFT:** EC9 136 1x2 tex
- **Length:** 9 ft
- **Width:** 10 ft
- **Weight as per ASTM-D3776-2009:** 6 g / m²
- **Ounces per Square Yard:** 18
- **Thickness as per ASTM-D1777-1996:** 0.7 mm
- **Thread count per cm as per ASTM-D3775-2008:** **WARP:** 18; **WEFT:** 13
- **Coating:** Uncoated, Tan
- **Total Weight as per ASTM-D3776-2009:** 680 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 0.7 mm
- **Tensile Strength as per ASTM-D5034-2001:** **WARP:** 2500 N/2.5 cm; **WEFT:** 1500 N/2.5 cm
- **Continuous Use Temperature:** 1652° F (900° C)
- **Melt Point Temperature:** 2732° F (1500° C)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, American FM/ANSI 4950