



AGMAT48X72HD

Armour Guard Heavy Duty FR Rubber Fatigue Mat

Features

- Heavy Duty
- Black Nitrile Rubber Top Surface has 20% Recycled Content
- Closed-cell nitrile blended cushion is permanently molded to the nitrile rubber top surface
- Chemical-resistant, grease and oil-resistant; borders will not crack or curl
- · Welding Safe and Electrically Conductive
- · Certified slip resistant by National Floor Safety Institute
- · Borders are beveled

Technical Specifications

- Surface Material: Nitrile Rubber
- Cushion Material: High-density, closed-cell nitrile/PVC-blended foam.
- Color: Black
- Size: 48" x 72"
- Thickness: 7/8"
- Packaging: Packaged by the Individual Mat
- . Country of origin: United States

Applications

 Distribution, Manufacturing, and Retail Facilities for Picking Lines, Assembly Lines, Workstations, and Check-Out Stations

Standards and Testing

- Passes Flammability standard BS-4790 Metal nut Method
- Certified high-traction by the National Floor Safety Institute (NFSI)
- . ESD rating of electrically conductive
- Compression Deflection: 7/8" Mat: 51.0% at 20 psi, 66.0% at 40
- ASTM C1028-96 static coefficient of friction
 - o Dry: 0.87
 - Wet: 0.85

