TECHNIWELDUSA



AGMAT36X60HD Armour Guard Heavy Duty FR Rubber

Fatigue Mat

Features	Technical Specifications
 Heavy Duty Black Nitrile Rubber Top Surface has 20% Recycled Content Closed-cell nitrile blended cushion is permanently molded to the nitrile rubber top surface Chemical-resistant, grease and oil-resistant; borders will not crack or curl Welding Safe and Electrically Conductive Certified slip resistant by National Floor Safety Institute Borders are beveled 	 Surface Material: Nitrile Rubber Cushion Material: High-density, closed-cell nitrile/PVC-blended foam Color: Black Size: 36" x 60" Thickness: 7/8" Packaging: Packaged by the Individual Mat Country of origin: United States
Applications • Distributing, Manufacturing, and Retail Facilities for Picking Lines, Assembly Lines, Workstations, and Check-Out Stations	 Passes Flammability standard BS-4790 Metal nut Method Certified high-traction by the National Floor Safety Institute (NFSI) ESD rating of electrically conductive Compression Deflection: 7/8" Mat: 51.0% at 20 psi, 66.0% at 40 psi ASTM C1028-96 static coefficient of friction Dry: 0.87 Wet: 0.85

TECHNIWELDUSA TWUSA.com

6205 Boat Rock Blvd. SW, Atlanta, Georgia 30336-2727