



# AGMAT36X60

## Armour Guard FR Rubber Fatigue Mat

### Features

- Black Nitrile Rubber Top Surface has 20% Recycled Content
- Closed-cell nitrile blended cushion is permanently molded to the nitrile rubber top surface
- Chemical-resistant, grease and oil-resistant; borders will not crack or curl
- Welding Safe and Electrically Conductive
- Certified slip resistant by National Floor Safety Institute
- Borders are beveled

### Applications

- Distribution, Manufacturing, and Retail Facilities for Picking Lines, Assembly Lines, Workstations, and Check-Out Stations

### Technical Specifications

- **Surface Material:** Nitrile Rubber
- **Cushion Material:** High-density, closed-cell nitrile/PVC-blended foam
- **Color:** Black
- **Size:** 36" x 60"
- **Thickness:** 5/8"
- **Packaging:** Packaged by the Individual Mat
- **Country of origin:** United States

### Standards and Testing

- Passes Flammability standard BS-4790 Metal nut Method
- Certified high-traction by the National Floor Safety Institute (NFSI)
- ESD rating of electrically conductive
- Compression Deflection: 5/8" Mat: 47.8% at 20 psi, 61.6% at 40 psi
- ASTM C1028-96 static coefficient of friction
  - Dry: 0.87
  - Wet: 0.85