



HSI12XRL

1/2" X 600' Red Air & Water Hose Reel

Features

- Premium Flexible Gas Hose
- Premium Burst Resistant Fibered composition
- American Quality Control
- Ozone Resistant
- Aging Resistant
- Limited Oil Resistance (Acetylene Only)

Technical Specifications

- **Tube Material:** SBR+NR Compound
- **Cover Material:** EPDM Compound
- **Cover:** Corrugated
- **Reinforced:** Spiral Polyester Yarns
- **Working Pressure:** 300 PSI
- **Burst Pressure:** 900 PSI
- **Inner Diameter:** 1/2" (12.7 mm)
- **Outer Diameter:** .775" (19.7 mm)
- **Length:** 600'
- **Inner and Outer Diameter Tolerance:** 0.5 mm
- **Temperature Range:** -22° F (-30° C) – 176° F (80° C)
- **Color:** Red
- **For Use With:** Acetylene
- **Compliance:** BS EN ISO2398:2016 Type 2, Class A, Category N-T

Applications

- Manufacturing – Architectural and Structural Metals, Mining, Agricultural, Motor Vehicles, Aerospace, Shipbuilding
- Construction – Residential, Commercial, Bridges, Dams, Utilities
- Or any other industry where welders may work

Usage Instructions

- Connect the hose to the regulator and torch body.
- Tighten all connection nuts firmly with a wrench making sure the system is leak-tight.